

Package ‘BetterReg’

February 1, 2026

Type Package
Title Better Statistics for OLS and Binomial Logistic Regression
Version 0.3.0
Maintainer Chris Aberson <chris.aberson@gmail.com>
Description Provides squared semi partial correlations, tolerance, Mahalanobis, Likelihood Ratio Chi Square, and Pseudo R Square. Aberson, C. L. (2022) <[doi:10.31234/osf.io/s2yqn](https://doi.org/10.31234/osf.io/s2yqn)>.
License GNU General Public License version 3
Encoding UTF-8
LazyData true
Imports car (>= 3.0-0), stats (>= 3.5.0), dplyr (>= 0.8.0)
Depends R (>= 3.5.0)
RoxygenNote 7.3.3
NeedsCompilation no
Author Chris Aberson [aut, cre]
Repository CRAN
Date/Publication 2026-02-01 08:30:11 UTC

Contents

depbcomp	2
indbcomp	3
LRchi	3
Mahal	5
parts	5
pseudo	6
R2change	6
sample1	7
sample2	8
testlog	8
testreg	9
tolerance	9
Index	10

depbcomp	<i>Power for Comparing Dependent Coefficients in Multiple Regression with Two or Three Predictors Requires correlations between all variables as sample size. Means, sds, and alpha are option. Also computes Power(All)</i>
----------	--

Description

Power for Comparing Dependent Coefficients in Multiple Regression with Two or Three Predictors Requires correlations between all variables as sample size. Means, sds, and alpha are option. Also computes Power(All)

Usage

```
depbcomp(
  data = NULL,
  y = NULL,
  x1 = NULL,
  x2 = NULL,
  x3 = NULL,
  x4 = NULL,
  x5 = NULL,
  numpred = NULL,
  comps = "abs"
)
```

Arguments

data	name of data file
y	dependent variable name
x1	first predictor variable name
x2	second predictor variable name
x3	third predictor variable name
x4	fourth predictor variable name
x5	fifth predictor variable name
numpred	number of predictors
comps	Type of comparison, "abs" for absolute values or "raw" for raw coefficients

Value

Comparing Dependent Coefficients in Multiple Regression

Examples

```
depbcomp(data=testreg,y="y",x1="x1",x2="x2",x3="x3",x4="x4",x5="x5", numpred=5,comps="abs")
```

indbcomp

*Comparing Independent Coefficients in Multiple Regression***Description**

Comparing Independent Coefficients in Multiple Regression

Usage

```
indbcomp(model1 = NULL, model2 = NULL, comps = "abs", pred = NULL)
```

Arguments

model1	Summary of first model (see example for how to summarize)
model2	Summary of second model (see example for how to summarize)
comps	Type of comparison. "abs" - absolute value of coefficient
pred	Number of predictors

Value

Comparing Independent Coefficients in Multiple Regression

Examples

```
y_1<-rnorm(200); x1_1<-rnorm(200); x2_1<-rnorm(200)
y_2<-rnorm(200); x1_2<-rnorm(200); x2_2<-rnorm(200)
df1<-as.data.frame(cbind(y_1, x1_1,x2_1))
df2<-as.data.frame(cbind(y_2, x1_2,x2_2))
model1_2<-summary(lm(y_1~x1_1+x2_1, data=df1))
model2_2<-summary(lm(y_2~x1_2+x2_2, data=df2))
indbcomp(model1 = model1_2, model2 = model2_2, comps="abs", pred=2)
```

LRchi

*Compute Likelihood Ratio Chi-square for Binomial Logistic Regression with up to 10 predictors***Description**

Compute Likelihood Ratio Chi-square for Binomial Logistic Regression with up to 10 predictors

Usage

```
LRchi(  
  data = NULL,  
  y = NULL,  
  x1 = NULL,  
  x2 = NULL,  
  x3 = NULL,  
  x4 = NULL,  
  x5 = NULL,  
  x6 = NULL,  
  x7 = NULL,  
  x8 = NULL,  
  x9 = NULL,  
  x10 = NULL,  
  numpred = NULL  
)
```

Arguments

data	name of your datafile, loaded
y	dependent variable name
x1	first predictor variable name
x2	second predictor variable name
x3	third predictor variable name
x4	fourth predictor variable name
x5	fifth predictor variable name
x6	sixth predictor variable name
x7	seventh predictor variable name
x8	eighth predictor variable name
x9	ninth predictor variable name
x10	tenth predictor variable name
numpred	number of predictors

Examples

```
LRchi(data=testlog, y="dv", x1="iv1", x2="iv2", numpred=2)
```

Mahal	<i>Compute Mahalanobis Distance for Multiple Regression</i>
-------	---

Description

Compute Mahalanobis Distance for Multiple Regression

Usage

```
Mahal(model = NULL, pred = NULL, values = 5)
```

Arguments

model	name of model
pred	number of predictors
values	number of Mahal values to print (highest values). Default is 10

Value

Mahalanobis Distance to detect MV outliers

Examples

```
mymodel<-lm(y~x1+x2+x3+x4, testreg)
Mahal(model=mymodel, pred=5, values = 10)
```

parts	<i>Compute squared semi partial correlations for Multiple Regression</i>
-------	--

Description

Compute squared semi partial correlations for Multiple Regression

Usage

```
parts(model = NULL, pred = NULL)
```

Arguments

model	name of model
pred	number of predictors

Value

Squared semipartial correlations for MRC with up to 10 predictors

Examples

```
mymodel<-lm(y~x1+x2+x3+x4+x5, data=testreg)
parts(model=mymodel, pred=5)
```

pseudo	<i>Pseudo R-square Values for Binomial Logistic Regression</i>
--------	--

Description

Pseudo R-square Values for Binomial Logistic Regression

Usage

```
pseudo(model = NULL)
```

Arguments

model name of model

Value

Pseudo R-square Values for Logistic Regression

Examples

```
mymodel<-glm(dv~iv1+iv2+iv3+iv4, testlog,family = binomial())
pseudo(model=mymodel)
```

R2change	<i>R-square change for Hierarchical Multiple Regression</i>
----------	---

Description

R-square change for Hierarchical Multiple Regression

Usage

```
R2change(model1 = NULL, model2 = NULL)
```

Arguments

model1 first regression model
model2 second regression model

Examples

```
mymodel1<-lm(y~x1+x2, data=testreg)
mymodel2<-lm(y~x1+x2+x3+x4, data=testreg)
R2change(model1=mymodel1, model2=mymodel2)
```

sample1	<i>sample1</i>
---------	----------------

Description

A dataset to test comparisons between independent coefficients

Usage

```
sample1
```

Format

A data frame with 713 rows and 14 variables:

- id** ID
- AA_DV** Dependent variable
- AA_Initial** 1st predictor
- merit** 2nd predictor
- discrim** 3rd predictor
- pers_exp** 4th predictor
- liberal** 5th predictor
- female** 6th predictor
- economic** 7th predictor
- div_part** 8th predictor
- pers_expN** 9th predictor
- liberalN** 10th predictor
- femaleN** 11th predictor
- economicN** 12th predictor

sample2	<i>sample2</i>
---------	----------------

Description

A dataset to test logistic regression functions

Usage

sample2

Format

A data frame with 164 rows and 11 variables:

- AA_DV** Dependent variable
- div_part** 1st predictor
- merit** 2nd predictor
- discrim** 3rd predictor

testlog	<i>testlog</i>
---------	----------------

Description

A dataset to test logistic regression functions

Usage

testlog

Format

A data frame with 164 rows and 11 variables:

- dv** DV
- iv1** 1st predictor
- iv2** 2nd predictor
- iv3** 3rd predictor
- iv4** 4th predictor
- iv5** 5th predictor
- iv6** 6th predictor
- iv7** 7th predictor
- iv8** 8th predictor
- iv9** 9th predictor
- iv10** 10th predictor

testreg	<i>testreg</i>
---------	----------------

Description

A dataset to test regression functions

Usage

testreg

Format

A data frame with 1000 rows and 6 variables:

- y DV
- x1 1st predictor
- x2 2nd predictor
- x3 3rd predictor
- x4 4th predictor
- x5 5th predictor

tolerance	<i>Compute tolerance for Multiple Regression</i>
-----------	--

Description

Compute tolerance for Multiple Regression

Usage

tolerance(model = NULL)

Arguments

model name of model

Value

Tolerance for MR

Examples

```
mymodel<-lm(y~x1+x2+x3+x4+x5, data=testreg)
tolerance(model=mymodel)
```

Index

* datasets

sample1, [7](#)

sample2, [8](#)

testlog, [8](#)

testreg, [9](#)

depbcomp, [2](#)

indbcomp, [3](#)

LRchi, [3](#)

Mahal, [5](#)

parts, [5](#)

pseudo, [6](#)

R2change, [6](#)

sample1, [7](#)

sample2, [8](#)

testlog, [8](#)

testreg, [9](#)

tolerance, [9](#)