

# The rotchiffre package

Heiko Oberdiek\*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.1

## Abstract

This package implements chiffres ROT13 with its variants ROT5, ROT18, and ROT47.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Motivation	2
1.2	Usage	2
1.2.1	Examples	2
<b>2</b>	<b>Implementation</b>	<b>3</b>
2.1	Reload check and package identification	3
2.2	Catcodes	4
2.3	Loading resources	5
2.4	\EdefRot as robust macro	5
2.5	Set \lccode on a range of characters	5
2.6	Chiffres	6
2.6.1	ROT13	6
2.6.2	ROT5	7
2.6.3	ROT18	7
2.6.4	ROT47	7
2.7	\RotCh@rot with big char support	7
2.8	\RotCh@rot without big char support	8
<b>3</b>	<b>Test</b>	<b>8</b>
3.1	Catcode checks for loading	8
3.2	Macro tests	10
3.2.1	Preamble	10
3.2.2	ROT13	13
3.2.3	ROT5	13
3.2.4	ROT18	13
3.2.5	ROT47	13
3.2.6	Big chars	14
<b>4</b>	<b>Installation</b>	<b>14</b>
4.1	Download	14
4.2	Bundle installation	15
4.3	Package installation	15
4.4	Refresh file name databases	15
4.5	Some details for the interested	15
<b>5</b>	<b>Catalogue</b>	<b>16</b>

---

\*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

<b>6</b>	<b>References</b>	<b>16</b>
<b>7</b>	<b>History</b>	<b>17</b>
	[2010/11/12 v1.0] . . . . .	17
	[2016/05/16 v1.1] . . . . .	17
<b>8</b>	<b>Index</b>	<b>17</b>

# 1 Documentation

## 1.1 Motivation

In the newsgroup `comp.text.tex` there was a discussion [1] about package `fontspec`. Stephan Hennig provided an example to implement ROT13 as OpenType feature [2]. And Robin Fairbairns requested a CTAN upload [3] ☺.

But I think it would be not fair to the users of old T<sub>E</sub>X engines without OpenType support that they will not be able to decrypt texts generated by the new package ☺. Therefore I have written this package that implements ROT13 even for ini-T<sub>E</sub>X. Also other variants ROT5, ROT18, ROT47 are provided.

## 1.2 Usage

`\EdefRot {⟨type⟩} {⟨cmd⟩} {⟨text⟩}`

The `⟨text⟩` is expanded and sanitized. All tokens are letters with catcode 12 (other with the exeption of the space token that has character code 32 (0x20) and catcode 10 (space). This follows T<sub>E</sub>X's convention of `\string` and `\meaning`.

The chiffre type is specified by `⟨type⟩` it takes a number. For example, ROT13 is specified by 13. The selected chiffre is applied to `⟨text⟩` and the result is stored in macro `⟨cmd⟩`.

The following table lists the supported rotation chiffres.

chiffre	from	to
<b>ROT13</b>	A-Z	N-Z A-M
	a-z	n-z a-m
<b>ROT5</b>	0-9	5-9 0-4
<b>ROT18</b>	A-Z 0-9	S-Z 0-9 A-R
	a-z	n-z a-m
<b>ROT47</b>	!-~	P-~ !-O

In case of ROT47 the range is the ASCII range from character codes 33 (0x21) ‘!’ upto 126 (0xFE) ‘~’.

The specifications of the algorithms are taken from the description in Wikipedia [4, 5], ROT18 is further specified by “computerfreak” [6].

### 1.2.1 Examples

The famous English pangram [7] is converted by

```
\EdefRot{13}\result{The quick brown fox jumps over the lazy dog}
```

The result is stored in macro `\result` with the following contents:

```
Gur dhvpx oebja sbk whzcf bire gur ynml qbt
```

Command names are converted to strings before. Therefore the text should not contain T<sub>E</sub>X markup, example:

```

\edefRot{13}\result{\texttt{Hello}\par\textit{World}}
\result → Uryyb\mqinapr \cne@qrnguplpyrf \@ar Jbeyq

```

But macros can be used that contain text. They are expanded.

```

\newcommand{\Name}{Heiko}
\newcommand{\Email}{heiko.oberdiek at gmail.com}
\edefRot{13}\result{Hello \Name\space\Email}
\result → Uryyb Urvxb <urvxb.boreqvr ng tbbtyrznvy.pbz>

```

## 2 Implementation

```
1 (*package)
```

### 2.1 Reload check and package identification

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```

2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@rotchiffre.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{rotchiffre}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @

```

```

46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[{#3}]%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@rotchiffre.sty\endcsname
67 \ProvidesPackage{rotchiffre}%
68 [2016/05/16 v1.1 Perform simple rotation ciphers (HO)]%

```

## 2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname RotCh@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95 \edef\RotCh@AtEnd{%
96 \RotCh@AtEnd
97 \catcode#1=\the\catcode#1\relax
98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{42}{12}% *
102 \TMP@EnsureCode{43}{12}% +
103 \TMP@EnsureCode{45}{12}% -
104 \TMP@EnsureCode{46}{12}% .

```

```

105 \TMP@EnsureCode{47}{12}% /
106 \TMP@EnsureCode{60}{12}% <
107 \TMP@EnsureCode{62}{12}% >
108 \TMP@EnsureCode{91}{12}% [
109 \TMP@EnsureCode{93}{12}% ]
110 \TMP@EnsureCode{96}{12}% `
111 \edef\RotCh@AtEnd{\RotCh@AtEnd\noexpand\endinput}

```

## 2.3 Loading resources

```

112 \begingroup\expandafter\expandafter\expandafter\endgroup
113 \expandafter\ifx\cename RequirePackage\endcsname\relax
114 \input infwarerr.sty\relax
115 \input ltxcmds.sty\relax
116 \input pdfescape.sty\relax
117 \else
118 \RequirePackage{infwarerr}[2010/04/08]%
119 \RequirePackage{ltxcmds}[2010/03/01]%
120 \RequirePackage{pdfescape}[2010/03/01]%
121 \fi

```

## 2.4 \EdefRot as robust macro

The main macro `\EdefRot` is made robust if  $\varepsilon$ -TeX or L<sup>A</sup>T<sub>E</sub>X are present.

`\EdefRot`

```

122 \ltx@ifundefined{protected}{%
123 \ltx@ifundefined{DeclareRobustCommand}{%
124 \def\RotCh@temp{\def\EdefRot##1}%
125 }{%
126 \def\RotCh@temp{\DeclareRobustCommand*\EdefRot[1]}%
127 }%
128 }{%
129 \def\RotCh@temp{\protected\def\EdefRot##1}%
130 }
131 \RotCh@temp{%
132 \RotCh@GetNumber{#1}%
133 \ltx@ifundefined{RotCh@rot@\romannumeral\RotCh@number}{%
134 \@PackageError{rotchiffre}{%
135 Unknown chiffre ROT\RotCh@number
136 }\@ehc
137 \EdefSanitize
138 }{%
139 \RotCh@rot
140 }%
141 }

```

`\RotCh@GetNumber` If  $\varepsilon$ -TeX is active, then the chiffre number can be an expression supported by `\numexpr`.

```

142 \ltx@ifundefined{numexpr}{%
143 \def\RotCh@GetNumber#1{%
144 \edef\RotCh@number{\number#1}%
145 }%
146 }{%
147 \def\RotCh@GetNumber#1{%
148 \edef\RotCh@number{\the\numexpr#1\relax}%
149 }%
150 }

```

## 2.5 Set \lccode on a range of characters

`\RotCh@count`

```

151 \countdef\RotCh@count=255 %

```

```

\RotCh@count@end
152 \countdef\RotCh@count@end=2 %

RotCh@RangeIgnore
153 \def\RotCh@RangeIgnore{%
154   \RotCh@loop{%
155     \lccode\RotCh@count=\ltx@zero
156   }%
157 }

\RotCh@RangeSet
158 \ltx@ifundefined{numexpr}{%
159   \countdef\RotCh@count@temp=4 %
160   \def\RotCh@RangeSet#1{%
161     \RotCh@loop{%
162       \RotCh@count@temp=\RotCh@count
163       \advance\RotCh@count@temp #1 %
164       \lccode\RotCh@count=\RotCh@count@temp
165     }%
166   }%
167 }{%
168   \def\RotCh@RangeSet#1{%
169     \RotCh@loop{%
170       \lccode\RotCh@count=\numexpr\RotCh@count#1\relax
171     }%
172   }%
173 }

\RotCh@loop
174 \def\RotCh@loop#1#2#3{%
175   \RotCh@count=#2 %
176   \RotCh@count@end=#3 %
177   \def\RotCh@action{#1}%
178   \RotCh@@loop
179 }%

RotCh@@loop
180 \def\RotCh@@loop{%
181   \RotCh@action
182   \ifnum\RotCh@count<\RotCh@count@end
183     \advance\RotCh@count\ltx@one
184     \expandafter\RotCh@@loop
185   \fi
186 }

```

## 2.6 Chiffres

### 2.6.1 ROT13

```

\RotCh@rot@xiii
187 \def\RotCh@rot@xiii{%
188   \RotCh@RangeIgnore{0}{64}%
189   \RotCh@RangeSet{+13}{65}{77}%
190   \RotCh@RangeSet{-13}{78}{90}%
191   \RotCh@RangeIgnore{91}{96}%
192   \RotCh@RangeSet{+13}{97}{109}%
193   \RotCh@RangeSet{-13}{110}{122}%
194   \RotCh@RangeIgnore{123}{255}%
195 }

```

## 2.6.2 ROT5

```
\RotCh@rot@v
196 \def\RotCh@rot@v{%
197 \RotCh@RangeIgnore{0}{47}%
198 \RotCh@RangeSet{+5}{48}{52}%
199 \RotCh@RangeSet{-5}{53}{57}%
200 \RotCh@RangeIgnore{58}{255}%
201 }
```

## 2.6.3 ROT18

```
\RotCh@rot@xviii
202 \def\RotCh@rot@xviii{%
203 \RotCh@RangeIgnore{0}{47}%
204 \RotCh@RangeSet{+25}{48}{57}%
205 \RotCh@RangeIgnore{58}{64}%
206 \RotCh@RangeSet{+18}{65}{72}%
207 \RotCh@RangeSet{-25}{73}{82}%
208 \RotCh@RangeSet{-18}{83}{90}%
209 \RotCh@RangeIgnore{91}{96}%
210 \RotCh@RangeSet{+13}{97}{109}%
211 \RotCh@RangeSet{-13}{110}{122}%
212 \RotCh@RangeIgnore{123}{255}%
213 }
```

## 2.6.4 ROT47

```
\RotCh@rot@xlvi
214 \def\RotCh@rot@xlvi{%
215 \RotCh@RangeIgnore{0}{32}%
216 \RotCh@RangeSet{+47}{33}{79}%
217 \RotCh@RangeSet{-47}{80}{126}%
218 \RotCh@RangeIgnore{127}{255}%
219 }
```

## 2.7 \RotCh@rot with big char support

Some modern T<sub>E</sub>X engines support characters with more than eight bits (codes greater as 255). LuaT<sub>E</sub>X and X<sub>Y</sub>T<sub>E</sub>X are detected by the caret notation that is extended by these engines.

```
220 \begingroup
221 \catcode0=9 %
222 \catcode\^=7 %
223 \catcode\^^=12 %
224 \def\x{^^^^0000}%
225 \expandafter\endgroup
226 \ifx\x\ltx@empty
```

\RotCh@toks

```
227 \toksdef\RotCh@toks=0 %
```

\RotCh@rot

```
228 \long\def\RotCh@rot#1#2{%
229 \EdefSanitize#1{#2}%
230 \begingroup
231 \csname RotCh@rot@\romannumeral\RotCh@number\endcsname
232 \RotCh@toks={}%
233 \expandafter\RotCh@SplitSpace#1 \@nil
234 \expandafter\endgroup
235 \expandafter\def\expandafter#1\expandafter{%
```

```

236 \the\RotCh@toks
237 }%
238 }%

```

\RotCh@SplitSpace

```

239 \def\RotCh@temp#1{%
240 \def\RotCh@SplitSpace##1 ##2\@nil{%
241 \RotCh@Add##1\relax
242 \ifx\relax##2\relax
243 \expandafter\ltx@gobble
244 \else
245 \RotCh@toks\expandafter{\the\RotCh@toks#1}%
246 \expandafter\ltx@firstofone
247 \fi
248 {%
249 \RotCh@SplitSpace##2\@nil
250 }%
251 }%
252 }%
253 \RotCh@temp{ }%

```

\RotCh@Add

```

254 \def\RotCh@Add#1{%
255 \ifx#1\relax
256 \else
257 \ifnum`#1>126 %
258 \RotCh@toks\expandafter{\the\RotCh@toks#1}%
259 \else
260 \lowercase{%
261 \RotCh@toks\expandafter{\the\RotCh@toks#1}%
262 }%
263 \fi
264 \expandafter\RotCh@Add
265 \fi
266 }%
267 \else

```

## 2.8 \RotCh@rot without big char support

\RotCh@rot

```

268 \long\def\RotCh@rot#1#2{%
269 \EdefSanitize#1{#2}%
270 \begingroup
271 \csname RotCh@rot@\romannumeral\RotCh@number\endcsname
272 \lowercase\expandafter{\expandafter\endgroup
273 \expandafter\def\expandafter#1\expandafter{#1}%
274 }%
275 }%
276 \fi
277 \RotCh@AtEnd%
278 \end{package}

```

## 3 Test

### 3.1 Catcode checks for loading

```

279 \test1\
280 \catcode`\{=1 %
281 \catcode`\}=2 %

```



```

282 \catcode`\#=6 %
283 \catcode`\@=11 %
284 \expandafter\ifx\csname count@\endcsname\relax
285   \countdef\count@=255 %
286 \fi
287 \expandafter\ifx\csname @gobble\endcsname\relax
288   \long\def\@gobble#1{%
289 \fi
290 \expandafter\ifx\csname @firstofone\endcsname\relax
291   \long\def\@firstofone#1{#1}%
292 \fi
293 \expandafter\ifx\csname loop\endcsname\relax
294   \expandafter\@firstofone
295 \else
296   \expandafter\@gobble
297 \fi
298 {%
299   \def\loop#1\repeat{%
300     \def\body{#1}%
301     \iterate
302   }%
303   \def\iterate{%
304     \body
305     \let\next\iterate
306   \else
307     \let\next\relax
308   \fi
309   \next
310 }%
311 \let\repeat=\fi
312 }%
313 \def\RestoreCatcodes{}
314 \count@=0 %
315 \loop
316   \edef\RestoreCatcodes{%
317     \RestoreCatcodes
318     \catcode\the\count@=\the\catcode\count@\relax
319   }%
320 \ifnum\count@<255 %
321   \advance\count@ 1 %
322 \repeat
323
324 \def\RangeCatcodeInvalid#1#2{%
325   \count@=#1\relax
326   \loop
327     \catcode\count@=15 %
328     \ifnum\count@<#2\relax
329       \advance\count@ 1 %
330     \repeat
331 }
332 \def\RangeCatcodeCheck#1#2#3{%
333   \count@=#1\relax
334   \loop
335     \ifnum#3=\catcode\count@
336     \else
337       \errmessage{%
338         Character \the\count@\space
339         with wrong catcode \the\catcode\count@\space
340         instead of \number#3%
341       }%
342     \fi
343   \ifnum\count@<#2\relax

```

```

344 \advance\count@ 1 %
345 \repeat
346 }
347 \def\space{ }
348 \expandafter\ifx\csname LoadCommand\endcsname\relax
349 \def\LoadCommand{\input rotchiffre.sty\relax}%
350 \fi
351 \def\Test{%
352 \RangeCatcodeInvalid{0}{47}%
353 \RangeCatcodeInvalid{58}{64}%
354 \RangeCatcodeInvalid{91}{96}%
355 \RangeCatcodeInvalid{123}{255}%
356 \catcode`\@=12 %
357 \catcode`\=0 %
358 \catcode`\%=14 %
359 \LoadCommand
360 \RangeCatcodeCheck{0}{36}{15}%
361 \RangeCatcodeCheck{37}{37}{14}%
362 \RangeCatcodeCheck{38}{47}{15}%
363 \RangeCatcodeCheck{48}{57}{12}%
364 \RangeCatcodeCheck{58}{63}{15}%
365 \RangeCatcodeCheck{64}{64}{12}%
366 \RangeCatcodeCheck{65}{90}{11}%
367 \RangeCatcodeCheck{91}{91}{15}%
368 \RangeCatcodeCheck{92}{92}{0}%
369 \RangeCatcodeCheck{93}{96}{15}%
370 \RangeCatcodeCheck{97}{122}{11}%
371 \RangeCatcodeCheck{123}{255}{15}%
372 \RestoreCatcodes
373 }
374 \Test
375 \csname @@end\endcsname
376 \end
377 </test1>

```

## 3.2 Macro tests

### 3.2.1 Preamble

```

378 <*test2>
379 \catcode`\{=1 %
380 \catcode`\}=2 %
381 \catcode`\#=6 %
382 \catcode`\^=7 %
383 \font\rmfont=ec-lmtt10\relax
384 \rmfont
385 \showboxbreadth=10000 %
386 \showboxdepth=10000 %
387 \errorcontextlines=10000
388 \begingroup\expandafter\expandafter\expandafter\endgroup
389 \expandafter\ifx\csname RequirePackage\endcsname\relax
390 \input rotchiffre.sty\relax
391 \else
392 \RequirePackage{rotchiffre}[2016/05/16]%
393 \RequirePackage{ifluatex}[2010/03/01]%
394 \RequirePackage{ifxetex}[2010/09/12]%
395 \fi
396 \catcode`\@=11 %
397 \begingroup\expandafter\expandafter\expandafter\endgroup
398 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
399 \begingroup\expandafter\expandafter\expandafter\endgroup
400 \expandafter\ifx\csname detokenize\endcsname\relax
401 \def\strip@prefix#1->{%

```

```

402 \def\@onelevel@sanitize#1{%
403 \edef#1{%
404 \expandafter\strip@prefix\meaning#1%
405 }%
406 }%
407 \else
408 \def\@onelevel@sanitize#1{%
409 \edef#1{%
410 \detokenize\expandafter{#1}%
411 }%
412 }%
413 \fi
414 \fi
415 \def\msg#1{\immediate\write16}
416 \def\empty{}
417 \begingroup
418 \def\x#1{%
419 \def\space{#1}%
420 \def\spacesII{#1#1}%
421 \def\spacesIII{#1#1#1}%
422 \def\spacesIV{#1#1#1#1}%
423 }%
424 \expandafter\endgroup\x{ }

425 \def\PrintStr#1#2{%
426 \begingroup
427 \@onelevel@sanitize#2%
428 \msg{#1: [#2]}% hash-ok
429 \endgroup
430 }
431 \def\CheckResult{%
432 \PrintStr{Result}\StrResult
433 \ifx\StrExpect\StrResult
434 \msg{==> Ok}%
435 \else
436 \begingroup
437 \edef\x{\endgroup
438 \errmessage{Test failed (\chiffre)!}%
439 }\x
440 \fi
441 }
442 \long\def\test#1#2{%
443 \msg{}%
444 \begingroup
445 \setbox0=\hbox{%
446 \edef\StrInput{#1}%
447 \@onelevel@sanitize\StrInput
448 \PrintStr{ Input}\StrInput
449 \edef\StrExpect{#2}%
450 \@onelevel@sanitize\StrExpect
451 \PrintStr{Expect}\StrExpect
452 \action{#1}%
453 \CheckResult
454 }%
455 \ifdim\wd0=0pt %
456 \else
457 \showbox0 %
458 \fi
459 \endgroup
460 }
461 \def\cmd#1{%
462 \msg{* CMD: ROT#1}%
463 \def\chiffre{ROT#1}%

```

```

464 \def\action{\EdefRot{#1}\StrResult}%
465 }

466 \def\TestIgnore#1{%
467 \test{#1}{#1}%
468 }

469 \begingroup
470 \lccode`P=\%%
471 \lccode`B=\%%
472 \lccode`H=\#%
473 \lowercase{\endgroup
474 \def\PercentChar{P}%
475 \def\BackslashChar{B}%
476 \def\HashChar{H}%
477 }

478 \def\TestIf{%
479 \TestIgnore{%
480 \space!"\HashChar$\PercentChar&'()*+,-./%
481 ;;<=>?@%
482 [\BackslashChar]^_`%
483 \string{|\string}\string~%
484 }%
485 }

486 \begingroup
487 \catcode0=12 %
488 \lccode`A=1 %
489 \lccode`B=2 %
490 \lccode`C=3 %
491 \lccode`D=4 %
492 \lccode`E=5 %
493 \lccode`F=6 %
494 \lccode`G=7 %
495 \lccode`H=8 %
496 \lccode`I=9 %
497 \lccode`J=10 %
498 \lccode`K=11 %
499 \lccode`L=12 %
500 \lccode`M=13 %
501 \lccode`N=14 %
502 \lccode`O=15 %
503 \lccode`P=16 %
504 \lccode`Q=17 %
505 \lccode`R=18 %
506 \lccode`S=19 %
507 \lccode`T=20 %
508 \lccode`U=21 %
509 \lccode`V=22 %
510 \lccode`W=23 %
511 \lccode`X=24 %
512 \lccode`Y=25 %
513 \lccode`Z=26 %
514 \lccode`a=27 %
515 \lccode`b=28 %
516 \lccode`c=29 %
517 \lccode`d=30 %
518 \lccode`e=31 %
519 \lccode`f=127 %
520 \lccode`g=128 %
521 \lccode`h=129 %
522 \lccode`y=254 %
523 \lccode`z=255 %
524 \lowercase{\endgroup
525 \def\TestC{%

```

```

526 \TestIgnore{%
527 ^^@ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz%
528 }%
529 }%
530 \def\TestZ{%
531 \TestIgnore{^^@}%
532 }%
533 }

```

### 3.2.2 ROT13

```

534 \cmd{13}
535 \test{%
536 0123456789%
537 ABCDEFGHIJKLMNOPQRSTUVWXYZ%
538 abcdefghijklmnopqrstuvwxyz%
539 }{%
540 0123456789%
541 NOPQRSTUVWXYZABCDEFGHIJKLM%
542 nopqrstuvwxyzabcdefghijklm%
543 }
544 \TestI
545 \TestC
546 \test{}{}
547 \test{A}{N}
548 \test{N}{A}
549 \test{ }{ }
550 \test{0a}{0n}
551 \test{\spacesIV}{\spacesIV}
552 \test{{}}{}}
553 \test{\par}{\noexpand\cne}

```

### 3.2.3 ROT5

```

554 \cmd{5}
555 \test{%
556 0123456789%
557 ABCDEFGHIJKLMNOPQRSTUVWXYZ%
558 abcdefghijklmnopqrstuvwxyz%
559 }{%
560 5678901234%
561 ABCDEFGHIJKLMNOPQRSTUVWXYZ%
562 abcdefghijklmnopqrstuvwxyz%
563 }
564 \TestI
565 \TestC

```

### 3.2.4 ROT18

```

566 \cmd{18}
567 \test{%
568 ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789%
569 abcdefghijklmnopqrstuvwxyz%
570 }{%
571 STUVWXYZ0123456789ABCDEFGHIJKLMN%
572 nopqrstuvwxyzabcdefghijklm%
573 }
574 \TestI
575 \TestC

```

### 3.2.5 ROT47

```

576 \cmd{47}
577 \test{%
578 !"\HashChar$\PercentChar&'()*+,-./%
579 0123456789%

```

```

580 <=>?@%
581 ABCDEFGHIJKLMNOPQRSTUVWXYZ%
582 [\BackslashChar]^_`%
583 abcdefghijklmnopqrstuvwxyz%
584 \string{|\string}\string~%
585 }{%
586 PQRSTUVWXYZ%
587 [\BackslashChar]^_`%
588 abcdefghijklmnopqrstuvwxyz%
589 \string{|\string}\string~%
590 !\"HashChar$\PercentChar&'()*+,-./%
591 0123456789%
592 <=>?@%
593 ABCDEFGHIJKLMNO%
594 }
595 \TestZ
596 \TestC

```

### 3.2.6 Big chars

```

597 \chardef\temp=0 %
598 \begingroup\expandafter\expandafter\expandafter\endgroup
599 \expandafter\ifx\csname XeTeXrevision\endcsname\relax
600 \begingroup\expandafter\expandafter\expandafter\endgroup
601 \expandafter\ifx\csname RequirePackage\endcsname\relax
602 \input ifluatex.sty\relax
603 \else
604 \RequirePackage{ifluatex}[2010/03/01]%
605 \fi
606 \begingroup\expandafter\expandafter\expandafter\endgroup
607 \expandafter\ifx\csname luatexversion\endcsname\relax
608 \else
609 \chardef\temp=1 %
610 \fi
611 \else
612 \chardef\temp=1 %
613 \fi
614 \ifcase\temp
615 \csname @@end\expandafter\endcsname\expandafter\end
616 \fi

617 \msg{* Big chars}
618 \cmd{5}
619 \test{}{}
620 \test{ }{ }
621 \test{ 0 1 }{ 5 6 }
622 \begingroup
623 \lccode`A=300 %
624 \lccode`B=1000 %
625 \lccode`C=10000 %
626 \lowercase{\endgroup
627 \TestIgnore{ABC}%
628 \TestIgnore{x A By zC xAy AxB}%
629 }%

630 \csname @@end\endcsname\end
631 /test2)

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

---

<sup>1</sup><http://ctan.org/pkg/rotchiffre>

[CTAN:macros/latex/contrib/oberdiek/rotchiffre.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/rotchiffre.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

## 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

## 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T<sub>E</sub>X:

```
tex rotchiffre.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>rotchiffre.sty</code>	→ <code>tex/generic/oberdiek/rotchiffre.sty</code>
<code>rotchiffre.pdf</code>	→ <code>doc/latex/oberdiek/rotchiffre.pdf</code>
<code>test/rotchiffre-test1.tex</code>	→ <code>doc/latex/oberdiek/test/rotchiffre-test1.tex</code>
<code>test/rotchiffre-test2.tex</code>	→ <code>doc/latex/oberdiek/test/rotchiffre-test2.tex</code>
<code>rotchiffre.dtx</code>	→ <code>source/latex/oberdiek/rotchiffre.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 4.4 Refresh file name databases

If your T<sub>E</sub>X distribution (teT<sub>E</sub>X, mikT<sub>E</sub>X, ...) relies on file name databases, you must refresh these. For example, teT<sub>E</sub>X users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for docstrip (really, docstrip does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{rotchiffre.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex rotchiffre.dtx
makeindex -s gind.ist rotchiffre.idx
pdflatex rotchiffre.dtx
makeindex -s gind.ist rotchiffre.idx
pdflatex rotchiffre.dtx
```

## 5 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `rotchiffre.xml`.

```
632 (*catalogue)
633 <?xml version='1.0' encoding='us-ascii'?>
634 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
635 <entry datestamp='$Date$' modifier='$Author$' id='rotchiffre'>
636   <name>rotchiffre</name>
637   <caption>Perform simple rotation cyphers.</caption>
638   <authorref id='auth:oberdiek'>
639     <copyright owner='Heiko Oberdiek' year='2010'>
640       <license type='lpp1.3'>
641         <version number='1.1'>
642         <description>
643           The package defines a command <tt>\EdefRot</tt> that defines a
644           macro (whose name is given as an argument) to the rotation of the
645           given string. Available rotations are <tt>ROT13</tt> (for
646           letters), <tt>ROT5</tt> (for digits), <tt>ROT18</tt> (for digits
647           and letters together) and <tt>ROT47</tt> (for all ASCII
648           characters).
649         <p/>
650         The package is part of the
651         <xref refid='oberdiek'>oberdiek</xref> bundle.
652       </description>
653       <documentation details='Package documentation'
654         href='ctan:/macros/latex/contrib/oberdiek/rotchiffre.pdf'>
655       <ctan file='true' path='/macros/latex/contrib/oberdiek/rotchiffre.dtx'>
656       <miktex location='oberdiek'>
657       <texlive location='oberdiek'>
658       <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>
659     </entry>
660 </catalogue>
```

## 6 References

- [1] Stephan Hennig et. al.: *fontspec: no ligatures with Times New Roman*; newsgroup [comp.text.tex](#),



news:4cdbed27\$0\$6765\$9b4e6d93@newsspool3.arcor-online.net,  
2010-11-11.  
[http://groups.google.com/group/comp.text.tex/browse\\_thread/thread/6266f98e998ce333/d7b32e9dcc610c87](http://groups.google.com/group/comp.text.tex/browse_thread/thread/6266f98e998ce333/d7b32e9dcc610c87)

- [2] Stephan Hennig: *Re: fontspec: no ligatures with Times New Roman*;  
newsgroup [comp.text.tex](#),  
news:4cdc2abe\$0\$6762\$9b4e6d93@newsspool3.arcor-online.net, 2010-11-11.  
<http://groups.google.com/group/comp.text.tex/msg/d7b32e9dcc610c87>
- [3] Robin Fairbairns: *Re: fontspec: no ligatures with Times New Roman*;  
newsgroup [comp.text.tex](#), news:qf4obmua0v.fsf@sxp10.cl.cam.ac.uk,  
2010-11-12.  
<http://groups.google.com/group/comp.text.tex/msg/7c03e91407144704>
- [4] Wikipedia/German: *ROT13*; 2010-10-26. <http://de.wikipedia.org/wiki/ROT13>
- [5] Wikipedia/English: *ROT13*; 2010-11-11. <http://en.wikipedia.org/wiki/ROT13>
- [6] Computerfreak/German: *ROT-18*; 2010-04-12.  
<http://www.compufreak.info/2010/04/12/rot-18/>
- [7] Wikipedia/English: *The quick brown fox jumps over the lazy dog*; 2010-11-09.  
[http://en.wikipedia.org/wiki/The\\_quick\\_brown\\_fox\\_jumps\\_over\\_the\\_lazy\\_dog](http://en.wikipedia.org/wiki/The_quick_brown_fox_jumps_over_the_lazy_dog)

## 7 History

[2010/11/12 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

## 8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		A	
<code>\#</code> .....	282, 381, 472	<code>\action</code> .....	452, 464
<code>\%</code> .....	358, 470	<code>\advance</code> .....	163, 183, 321, 329, 344
<code>\@</code> .....	283, 356, 396	<code>\aftergroup</code> .....	29
<code>\@PackageError</code> .....	134	<b>B</b>	
<code>\@ehc</code> .....	136	<code>\B</code> .....	471
<code>\@firstofone</code> .....	291, 294	<code>\BackslashChar</code> .....	475, 482, 582, 587
<code>\@gobble</code> .....	288, 296	<code>\body</code> .....	300, 304
<code>\@nil</code> .....	233, 240, 249	<b>C</b>	
<code>\@onelevel@sanitize</code> .....		<code>\catcode</code> .....	2, 3, 5,
.....	402, 408, 427, 447, 450		6, 7, 8, 9, 10, 11, 12, 13, 33, 34,
<code>\@undefined</code> .....	58		36, 37, 38, 39, 40, 41, 42, 43, 44,
<code>\</code> .....	357, 471		45, 46, 47, 48, 49, 69, 70, 72, 73,
<code>\{</code> .....	280, 379		74, 78, 79, 80, 81, 82, 83, 84, 87,
<code>\}</code> .....	281, 380		88, 90, 91, 92, 93, 97, 99, 221,
<code>\^</code> .....	222, 223, 382		222, 223, 280, 281, 282, 283,

318, 327, 335, 339, 356, 357, 358, 379, 380, 381, 382, 396, 487	\LoadCommand . . . . . 349, 359	
\chardef . . . . . 597, 609, 612	\loop . . . . . 299, 315, 326, 334	
\CheckResult . . . . . 431, 453	\lowercase . . . . . 260, 272, 473, 524, 626	
\chiffre . . . . . 438, 463	\ltx@empty . . . . . 226	
\cmd . . . . . 461, 534, 554, 566, 576, 618	\ltx@firstofone . . . . . 246	
\cne . . . . . 553	\ltx@gobble . . . . . 243	
\count@ . . . . . 285, 314, 318, 320, 321, 325, 327, 328, 329, 333, 335, 338, 339, 343, 344	\ltx@ifUndefined 122, 123, 133, 142, 158	
\countdef . . . . . 151, 152, 159, 285	\ltx@one . . . . . 183	
\csname . . . . . 14, 21, 50, 66, 76, 113, 231, 271, 284, 287, 290, 293, 348, 375, 389, 398, 400, 599, 601, 607, 615, 630	\ltx@zero . . . . . 155	
<b>D</b>		
\DeclareRobustCommand . . . . . 126	<b>M</b>	
\detokenize . . . . . 410	\meaning . . . . . 404	
<b>E</b>		\msg . . . . . 415, 428, 434, 443, 462, 617
\EdefRot . . . . . 2, 122, 464, 643	<b>N</b>	
\EdefSanitize . . . . . 137, 229, 269	\next . . . . . 305, 307, 309	
\empty . . . . . 17, 18, 416	\number . . . . . 144, 340	
\end . . . . . 376, 615, 630	\numexpr . . . . . 148, 170	
\endcsname . . . . . 14, 21, 50, 66, 76, 113, 231, 271, 284, 287, 290, 293, 348, 375, 389, 398, 400, 599, 601, 607, 615, 630	<b>P</b>	
\endinput . . . . . 29, 111	\P . . . . . 470	
\endlinechar . . . . . 4, 35, 71, 77, 89	\PackageInfo . . . . . 26	
\errmessage . . . . . 337, 438	\par . . . . . 553	
\errorcontextlines . . . . . 387	\PercentChar . . . . . 474, 480, 578, 590	
<b>F</b>		\PrintStr . . . . . 425, 432, 448, 451
\font . . . . . 383	\protected . . . . . 129	
<b>H</b>		\ProvidesPackage . . . . . 19, 67
\H . . . . . 472	<b>R</b>	
\HashChar . . . . . 476, 480, 578, 590	\RangeCatcodeCheck . . . . . . 332, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371	
\hbox . . . . . 445	\RangeCatcodeInvalid . . . . . . 324, 352, 353, 354, 355	
<b>I</b>		\repeat . . . . . 299, 311, 322, 330, 345
\ifcase . . . . . 614	\RequirePackage . . . . . . 118, 119, 120, 392, 393, 394, 604	
\ifdim . . . . . 455	\RestoreCatcodes . . 313, 316, 317, 372	
\ifnum . . . . . 182, 257, 320, 328, 335, 343	\rmfont . . . . . 383, 384	
\ifx . . . . . 15, 18, 21, 50, 58, 61, 113, 226, 242, 255, 284, 287, 290, 293, 348, 389, 398, 400, 433, 599, 601, 607	\romannumeral . . . . . 133, 231, 271	
\immediate . . . . . 23, 52, 415	\RotCh@loop . . . . . 178, 180, 180, 184	
\input . . . . . 114, 115, 116, 349, 390, 602	\RotCh@action . . . . . 177, 181	
\iterate . . . . . 301, 303, 305	\RotCh@Add . . . . . 241, 254	
<b>L</b>		\RotCh@AtEnd . . . . . 95, 96, 111, 277
\lccode . . . . . 155, 164, 170, 470, 471, 472, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 623, 624, 625	\RotCh@count . . . . . 151, 155, 162, 164, 170, 175, 182, 183	
	\RotCh@count@end . . . . . 152, 176, 182	
	\RotCh@count@temp 159, 162, 163, 164	
	\RotCh@GetNumber . . . . . 132, 142	
	\RotCh@loop . . . . . 154, 161, 169, 174	
	\RotCh@number . . . . . . 133, 135, 144, 148, 231, 271	
	\RotCh@RangeIgnore . . . . . . 153, 153, 188, 191, 194, 197, 200, 203, 205, 209, 212, 215, 218	
	\RotCh@RangeSet . . . . . 158, 189, 190, 192, 193, 198, 199, 204, 206, 207, 208, 210, 211, 216, 217	
	\RotCh@rot . . . . . 139, 228, 268	
	\RotCh@rot@v . . . . . 196	
	\RotCh@rot@xiii . . . . . 187	
	\RotCh@rot@xlvii . . . . . 214	
	\RotCh@rot@xviii . . . . . 202	

\RotCh@SplitSpace	233, 239	\test	442, 467, 535, 546,
\RotCh@temp	124, 126, 129, 131, 239, 253		547, 548, 549, 550, 551, 552,
\RotCh@toks	227, 232, 236, 245, 258, 261		553, 555, 567, 577, 619, 620, 621
<b>S</b>		\TestC	525, 545, 565, 575, 596
\setbox	445	\TestI	478, 544, 564, 574
\showbox	457	\TestIgnore	466, 479, 526, 531, 627, 628
\showboxbreadth	385	\TestZ	530, 595
\showboxdepth	386	\the	77, 78,
\space	338, 339, 347, 419, 480		79, 80, 81, 82, 83, 84, 97, 148,
\spacesII	420		236, 245, 258, 261, 318, 338, 339
\spacesIII	421	\TMP@EnsureCode	94, 101, 102, 103,
\spacesIV	422, 551		104, 105, 106, 107, 108, 109, 110
\StrExpect	433, 449, 450, 451	\toksdef	227
\StrInput	446, 447, 448	<b>W</b>	
\strip@prefix	401, 404	\wd	455
\StrResult	432, 433, 464	\write	23, 52, 415
<b>T</b>		<b>X</b>	
\temp	597, 609, 612, 614	\x	14, 15, 18, 22, 26, 28, 51, 56, 66,
\Test	351, 374		75, 87, 224, 226, 418, 424, 437, 439